

CARPET TILE SPECIFICATION POP CULTURE: POP ART

| | |
|-------------------|---------------------------------------|
| Construction | : Tufted Multi-Level Loop |
| Pile Content | : 100% Nylon BCF |
| Dyeing Method | : Solution Dyed |
| Tufting Gauge | : 1/12 inch |
| Tufted Density | : 2,078 / Dm ² |
| Pile Weight | : 16 oz./sq.yd. (542 gram/sq.m.) |
| Pile Height | : 3 – 5 mm. |
| Primary Backing | : Non Woven Polyester Spunbond |
| Secondary Backing | : Glass Reinforced PVC |
| Pile Treatment | : Stain Protector and Soil Repellency |
| Tile Size | : 50 x 50 cm. |



Performance

| | |
|---------------------------------|---|
| Castor Chair Rating (BS EN 985) | : ≥ 2.4 Continuous use |
| Dimension Stability (BS EN 986) | : ≤ 0.15% |
| Static Electricity (AATCC 134) | : ≤ 3.0 kV, under standard test condition (70 F & 20% RH) |

Colour Fastness

| | |
|--------------------------------|-------------------|
| To Light (ISO 105 B02) | : 4 - 5 or better |
| To Rubbing Wet (ISO 105 – X12) | : Minimum 4 |
| To Rubbing Dry (ISO 105 – X12) | : Minimum 4 |

Flammability

| | |
|--|---|
| Hot Metal Nut Test (BS 4790) | : Low radius of effects of ignition |
| Flame Resistance (ASTM D 2859) | : Passes Methenamine Pill Test |
| Radiant Panel Test (ASTM E648) | : ≥ 0.45 watt/cm ² - Class I |
| Smoke Density (ASTM E662) | : ≤ 450 Dmc |
| Reaction to Fire Test (BS EN ISO 9239 – 1) | : Criteria Heat Flux ≥ 4.5 kW/m ² , Class C _{fl} – s1 |

Indoor Air Quality

All carpets and rugs produced by Carpets International Thailand. This product are certified through the Carpet & Rug Institute (CRI) Green Label Plus® certification program, as GLP1022

Tolerance

Carpets International Thailand PCL applies strict quality control at all stages of production, in compliance with ISO 9001. However, as carpet manufacturer is a complex series of operations, slight variations in the weights quoted must be expected. Specifications are subject to change without notice but this will not have detrimental effect on the performance of the product.

Installation Method

Checkerboard



Certification

