

CARPET TILE SPECIFICATION URBAN ELEMENTS: MEZZANINE

| | |
|-------------------|----------------------------------|
| Construction | : Tufted Multi-Level Loop |
| Pile Content | : 100% Polypropylene BCF |
| Dyeing Method | : Solution Dyed |
| Tufting Gauge | : 1/10 inch |
| Stitches / 10 cm. | : 44 |
| Tufted Density | : 1,732 / Dm ² |
| Pile Weight | : 19 oz./sq.yd. (644 gram/sq.m.) |
| Pile Height | : 3 – 5 mm. |
| Primary Backing | : Non Woven Polyester Spunbond |
| Secondary Backing | : Glass Reinforced PVC |
| Tile Size | : 50 x 50 cm. |



Performance

| | |
|-------------------------------------|---|
| Overall Classification (BS EN 1307) | : General |
| Castor Chair Rating (BS EN 985) | : ≥ 2.4 Continuous use |
| Dimension Stability (BS EN 986) | : ≤ 0.15% |
| Static Electricity (AATCC 134) | : ≤ 3.0 kV, under standard test condition (70 F & 20% RH) |

Colour Fastness

| | |
|--------------------------------|-------------------|
| To Light (ISO 105 B02) | : 4 - 5 or better |
| To Rubbing Wet (ISO 105 - X12) | : Minimum 4 |
| To Rubbing Dry (ISO 105 - X12) | : Minimum 4 |

Flammability

| | |
|--------------------------------|-------------------------------------|
| Hot Metal Nut Test (BS 4790) | : Low radius of effects of ignition |
| Flame Resistance (ASTM D 2859) | : Passes Methenamine Pill Test |

Tolerance

Carpets International Thailand PCL applies strict quality control at all stages of production, in compliance with ISO 9001. However, as carpet manufacturer is a complex series of operations, slight variations in the weights quoted must be expected. Specifications are subject to change without notice but this will not have detrimental effect on the performance of the product.

Installation Method

Checkerboard Vertical Stair Step Horizontal Stair Step

